

5

10

15

20

APPLICATION FOR UNITED STATES LETTERS PATENT

FOR A

TOILET ACCESSORY CONCEALMENT AND TOILET BOWL EVACUATION

25

APPARATUS

30

Specification: 23 Total Pages including Claims & Abstract

Claims: 20 Total Claims including 3 Independent and 17 Dependent Claims

Drawings: 12 Figures in 8 Drawing Sheets

35

Inventor: Eleanor French Spreitzer, a resident of Columbus, Ohio, USA, (A U.S. citizen)

40

Attorney: Docket No. 030205.004

Michael J. Gallagher

Gallagher & Dawsey Co., L.P.A. (Customer Number 34,142)

*Mailing Address*

1487 W. Fifth Ave., Box 226

Columbus, OH 43212-2403

45

Telephone: (614) 397-8909

Facsimile: (614) 542-0306

## TECHNICAL FIELD

The present invention relates to the field of water closet, or toilet, cleaning apparatus, in particular to a toilet accessory concealment and toilet bowl evacuation apparatus designed to conceal common bathroom accessories as well as provide one with limited knowledge of plumbing systems with a safe and effective way to reduce the water level in a toilet bowl to facilitate cleaning.

## BACKGROUND OF THE INVENTION

Cleaning the water closet, or toilet, in a home, business or other location can be an unpleasant and difficult task. It is frequently accomplished by placing a cleansing agent into the bowl of a toilet and scrubbing with a specially formed toilet brush to remove undesirable elements and mineral deposits from the bowl. This task is made more difficult by the fact that a modern toilet operates on a siphonic principle that maintains a predetermined water level in the bowl between flushes. This means that a person cleaning must contend with cleaning around a standing water line in order to thoroughly clean the bowl. Unsatisfactory attempts to date include placing the cleaning agent in the water, causing dilution of the cleaner, and then attempting to clean the standing water line, or else attempting to scrub during a flush cycle, which is not only brief in duration but also is draining the cleaning agent from the bowl at the same time the cleaner is attempting to work.

The present invention advances the art by providing convenient means to exploit the manner of operation of the modern flush toilet in order to lower the standing water line in the bowl, which allows thorough cleaning with relatively undiluted cleaner, during a quiescent state

of bowl operation, which can then easily be restored to the predetermined water line and normal operation.

### **SUMMARY OF INVENTION**

5           In its most general configuration, the present invention advances the state of the art with a variety of new capabilities and overcomes many of the shortcomings of prior devices in new and novel ways. In its most general sense, the present invention overcomes the shortcomings and limitations of the prior art in any of a number of generally effective configurations. The instant invention demonstrates such capabilities and overcomes many of the shortcomings of prior  
10   methods in new and novel ways.

          A review of the mechanism of the modern flush toilet helps to explain the operation of the instant invention. Most modern toilets operate on a siphonic principle in which a standing bowl of water is connected by an upwardly directed U-shaped trap, which acts as a siphon tube, to a drain line. When the water in the tank, restrained by a flush valve, is suddenly released into  
15   the bowl, the sudden onrush of water is sufficient to fill the siphon tube and begin the siphonic cycle. The water and contents of the bowl are sucked upwards through the trap and down the drain line. When the water in the bowl drains low enough, air is sucked into the drain line, the siphon is broken, and the flush cycle stops. Modern toilets are designed to then continue to fill an additional amount of water, slowly, into the bowl to restore the standing water line in the bowl.  
20   The amount of fill water, and the rate in which it enters the bowl, is such that it never completely fills the siphon tube.

          If, in contrast to initiating a flush cycle by flushing the tank mechanism, one pours a quantity of water quickly into the bowl, a similar flush cycle occurs. The bowl and siphon tube

fill, the siphonic cycle begins, and the water in the bowl is sucked through the trap. When the water drains sufficiently for air to break the siphon, the cycle stops. However, in this instance, there is no additional water entering the bowl from the tank, and the standing water remains at a lower level than that in the normal order of operation of the toilet. This exposes the former water  
5 line for easy cleaning, leaves a small amount of water at the bottom of the bowl to mix cleaner, and leaves the bowl in a quiescent state during the cleaning process. When cleaning is complete, a simple flush of the tank mechanism will evacuate the cleaning materials and bowl contents, and restore the water line to the normal predetermined level.

The toilet accessory concealment and toilet bowl evacuation apparatus of the present  
10 invention is designed to serve a multitude of functions in the bathroom. It may be used to house bathroom accessories such as a toilet brush and rolls of toilet paper. Additionally, various embodiments may also house a plunger, bars of soap, or additional wash cloths. The apparatus may also be used to vastly improve the ability to clean a toilet bowl. It may be used to rapidly introduce a predetermined volume of liquid into the toilet bowl to start siphonic action in the  
15 toilet. This procedure removes a majority of the initial toilet bowl liquid and a majority of the first predetermined volume of liquid that was poured into the bowl. By reducing the quantity of liquid in the toilet bowl one can better clean the interior of the toilet bowl.

The toilet accessory concealment and toilet bowl evacuation apparatus includes a water-tight primary compartment, a water-tight secondary compartment, and a cover configured to  
20 cooperate with the primary compartment and obscure the view of the inside of the primary compartment. The primary compartment is sized and configured to conveniently house a toilet brush, or other bathroom accessory, and retain a first predetermined quantity of liquid when the brush is not in the compartment. The secondary compartment is sized and configured to

conveniently house a roll of toilet paper, or other bathroom accessory, and retain a second predetermined quantity of liquid when the roll of toilet paper is not in the compartment.

The primary compartment has an interior and an exterior surface, and at least one sidewall. The interior surface has a plurality of indicia reflective of a volume of the

5 predetermined volume of liquid. The at least one sidewall has at least one gripping device to grip and handle the primary compartment. In one particular embodiment the size of the primary compartment is such that it permits the retention of at least 1.66 liters, as this quantity has been determined to provide adequate siphonic action in most toilets. The aforementioned indicia allow a user, after a brief trial and error experimentation, to know and to reproduce the optimal amount  
10 of water needed for operation in his or her own fixtures. Generally, the greatest dimension of the primary compartment is less than approximately 18 inches thereby permitting the primary compartment to be filled at a bathtub faucet.

As with the primary compartment, the secondary compartment has an interior and an exterior surface and at least one sidewall. The sidewall has at least one gripping device to grip  
15 and handle the secondary compartment. The secondary compartment is sized to releasably retain a roll of toilet paper, or other bathroom accessory, and contain a second predetermined quantity of liquid when the roll of toilet paper is removed. Generally the greatest dimension of secondary compartment is less than approximately 6 inches thereby permitting the secondary compartment to be filled at a lavatory faucet. The secondary compartment permits the apparatus to be equally  
20 effective whether utilized in a full bathroom, one having a bathtub or shower, or a half-bath, one only having a toilet and a lavatory. When used in a half-bath, since the primary compartment generally will not fit below a lavatory faucet in a lavatory bowl, the secondary compartment serves as an intermediary reservoir to transfer liquid from the lavatory faucet into the primary

compartment. The secondary compartment may also incorporate a roll elevator designed to separate the roll of toilet paper from the secondary compartment interior surface to help ensure that the toilet paper remains dry.

The primary compartment and secondary compartment gripping devices may be handles  
5 or may include an ergonomic gripping surface formed in the sidewalls. Additionally, the sidewalls may be formed to include spouts to aid in pouring.

The design of the apparatus is such that the primary compartment and the secondary compartment are to be stored and displayed together, thereby reducing clutter in the bathroom. As such, the primary and secondary compartments may interface with one another in any number  
10 of ways. For example, the compartments may simply rest on one another, or they may be formed such that one of the compartments is housed inside the other compartment. Additionally, the interface may be such that the compartments releasably lock together.

As previously mentioned, the cover is configured to cooperate with the primary compartment and obscure the view of the inside of the primary compartment. The cover may  
15 include a plurality of ventilation passages to permit air movement through the primary compartment thereby aiding in the drying of the brush and reducing the likelihood of mildew growth. Additionally, the cover may further include a ventilated openable compartment capable of releasably containing a replenishable quantity of air freshener.

The apparatus may further be formed such that the primary compartment, the secondary  
20 compartment, and the cover collectively appear as a decorative object. The decorative object may include, but is not limited to, variations representing houses, animals, candles, plants, a barber pole, and toy figurines, just to name a few.

Accordingly, the art has needed a simple and convenient apparatus that may serve multiple uses in the bathroom including providing a method for quickly and easily reducing the amount of liquid in a toilet bowl to facilitate improved cleaning.

5

### BRIEF DESCRIPTION OF THE DRAWINGS

Without limiting the scope of the present invention as claimed below and referring now to the drawings and figures:

FIG. 1 shows the apparatus of the present invention in cross-section view, not to scale;

FIG. 2 shows the apparatus of FIG. 1 in top plan view, not to scale;

10

FIG. 3 shows the apparatus of FIG. 1 in side elevation view, not to scale;

FIG. 4 shows an embodiment of the apparatus of FIG. 1 in cross-section view, not to scale;

FIG. 5 shows an embodiment of the apparatus of FIG. 1 in cross-section view, not to scale;

15

FIG. 6 shows the primary compartment of the present invention in use, not to scale;

FIG. 7 shows the primary compartment of the present invention in use, not to scale;

FIG. 8 shows an embodiment of the apparatus of FIG. 1 in side elevation view, not to scale;

20

FIG. 9 shows an embodiment of the apparatus of FIG. 1 in cross-section view, not to scale;

FIG. 10 shows an embodiment of the apparatus of FIG. 1 in cross-section view, not to scale;

FIG. 11 shows an embodiment of the apparatus of FIG. 1 in cross-section view, not to scale; and

FIG. 12 shows an embodiment of the apparatus of FIG. 1 in side elevation view, not to scale.

5 Also, in the various figures and drawings, the following reference symbols and letters are used to identify the various elements described herein below in connection with the several figures and illustrations: B, BU, T, TB, TP, TR, W, and WL.

#### DETAILED DESCRIPTION OF THE INVENTION

10 The toilet accessory concealment and toilet bowl evacuation apparatus of the instant invention enables a significant advance in the state of the art. The preferred embodiments of the apparatus accomplish this by new and novel arrangements of elements and methods that are configured in unique and novel ways and which demonstrate previously unavailable but preferred and desirable capabilities.

15 The detailed description set forth below in connection with the drawings is intended merely as a description of the presently preferred embodiments of the invention, and is not intended to represent the only form in which the present invention may be constructed or utilized. The description sets forth the designs, functions, means, and methods of implementing the invention in connection with the illustrated embodiments. It is to be understood, however,  
20 that the same or equivalent functions and features may be accomplished by different embodiments that are also intended to be encompassed within the spirit and scope of the invention.



The toilet accessory concealment and toilet bowl evacuation apparatus **50** is designed to serve a multitude of functions in the bathroom. It may be used to house at least one toilet brush **B**, and may further be used to house at least one roll of toilet paper **TP**, as seen in FIG. 1. The apparatus **50** may additionally be used to rapidly introduce a first predetermined volume of liquid into a toilet bowl **TB** thereby starting siphonic action in the toilet **T** and removing a majority of the initial toilet bowl liquid and a majority of the first predetermined quantity of liquid, as seen in FIG. 6 and FIG. 7. By reducing the quantity of liquid in the toilet bowl **TB** one can better clean the interior of the toilet bowl **TB**.

Referring again to FIG. 1, in one embodiment the toilet accessory concealment and toilet bowl evacuation apparatus **50** includes a water-tight primary compartment **100**, a water-tight secondary compartment **200**, and a cover **300** configured to cooperate with the primary compartment **100** and obscure the view of the inside of the primary compartment **100**. The primary compartment **100** is sized and configured to conveniently house a toilet brush **B** and retain the first predetermined quantity of liquid when the brush **B** is not in the compartment **100**. The secondary compartment **200** is sized and configured to conveniently house a roll of toilet paper **TP** and retain a second predetermined quantity of liquid when the roll of toilet paper **TP** is not in the compartment **200**.

The primary compartment **100** has a closed proximal end **120** characterized by a base surface **130** and an open distal end **110**, as illustrated in FIG. 3. Referring now to FIG. 4, the primary compartment **100** has an interior and an exterior surface **150**, **160**, and at least one sidewall **140**. The interior surface **150** has a plurality of indicia **190** reflective of a volume of the predetermined volume of liquid. The at least one sidewall **140** has at least one gripping device **180**. In one particular embodiment the size of the primary compartment **100** permits the retention

of the first predetermined quantity of liquid of at least 1.66 liters, as this quantity has been determined to provide adequate siphonic action in most toilets **T**. In another embodiment the distance separating the primary compartment distal end **110** and the primary compartment proximal end **120** is less than approximately 18 inches thereby permitting the primary

5 compartment **100** to receive the first predetermined quantity of liquid from a bathtub faucet. In further embodiments, the at least one primary compartment gripping device **180** may be a handle **182**, shown in FIG. 4, or may include an ergonomic gripping surface **184**, seen in FIG. 8, formed in the at least one primary compartment sidewall **140**. The primary compartment gripping device **180** must provide a rigid secure interface between the user and the primary compartment **100**, as  
10 the primary compartment **100** will be relatively heavy once it contains the first predetermined quantity of liquid. Additionally, the at least one sidewall **140** of the primary compartment **100** may be formed to include a spout **170**.

Referring again to FIG. 3, the secondary compartment **200** has a closed proximal end **220** characterized by a base surface **230** and an open distal end **210**. The secondary compartment **200**  
15 has an interior and an exterior surface **250**, **260**, and at least one sidewall **240**, as seen in FIG. 5. The at least one sidewall **240** has at least one gripping device **280**, as indicated in FIG. 1. The secondary compartment **200** is sized to releasably retain a roll of toilet paper **TP** and contain a second predetermined quantity of liquid when the roll of toilet paper **TP** is removed. The secondary compartment **200** may be sized to releasably accommodate a removable divider **295**,  
20 seen in FIG. 4, to separate and protect the toilet paper **TP** or other article stored in the secondary compartment **200**. The removable divider **295** may have at least one gripping aperture to facilitate removal of the removable divider **295** from the secondary compartment **200**.

In one embodiment, a distance separating the secondary compartment distal end **210** and the secondary compartment proximal end **220** is less than approximately 6 inches thereby permitting the secondary compartment **200** to receive the second predetermined quantity of liquid from a lavatory faucet. The secondary compartment **200** permits the apparatus **50** to be  
5 equally effective whether utilized in a full bathroom, one having a bathtub or shower, or a half-bath, one only having a toilet **T** and a lavatory. When used in a half-bath, since the primary compartment **100** generally will not fit below a lavatory faucet in a lavatory bowl, the secondary compartment **200** serves as an intermediary reservoir to transfer liquid from the lavatory faucet into the primary compartment **100**.

10 In further embodiments, the at least one secondary compartment gripping device **280** may be a handle **282**, as seen in FIG. 4, or may include an ergonomic gripping surface **284** formed in the at least one primary compartment sidewall **240**, as seen in FIG. 8. Additionally, the at least one sidewall **240** of the secondary compartment **200** may be formed to include a spout **270**. In yet another embodiment illustrated in FIG. 5, the secondary compartment **200** may include a roll  
15 elevator **290** to separate the roll of toilet paper **TP** from the secondary compartment interior surface **250**.

The primary compartment **100** and the secondary compartment **200** may interface with one another in any number of ways. For example, in one embodiment, illustrated in FIG. 1, the proximal end **120** of the primary compartment **100** and the distal end **210** of the secondary  
20 compartment **200** cooperate so that the primary compartment **100** releasably mounts on the secondary compartment **200**. Alternatively, the proximal end **120** of the primary compartment **100** and the distal end **210** of the secondary compartment **200** cooperate so that the primary compartment **100** releasably mounts inside the secondary compartment **200**, as seen in FIG. 9. In

such an embodiment the secondary compartment interior surface **250** may be formed with at least one ledge **254** upon which the exterior surface **160** of the primary compartment **100** may rest, as illustrated in FIG. 5. Still further, the shape of the primary compartment **100** may cooperate with the secondary compartment **200** such that the secondary compartment **200** may  
5 releasably mount in the primary compartment **100**, as seen in FIG. 10.

The cover **300** is configured to cooperate with the primary compartment **100** and obscure the view of the inside of the primary compartment **100**, as seen in FIG. 1. The cover **300** may include a plurality of ventilation passages **320** to permit air movement through the primary compartment **100** thereby aiding in the drying of the brush **B** and reducing the likelihood of  
10 mildew growth, as seen in FIG. 2 and FIG. 4. Additionally, the cover **300** may incorporate a gripping device **310** to aide in the removal and installation of the cover **300**. Further, the cover **300** further includes a ventilated openable compartment capable of releasably containing a replenishable predetermined quantity of air freshener, as seen in FIG. 11.

The apparatus **50** may further be formed such that the primary compartment **100**, the  
15 secondary compartment **200**, and the cover **300** are formed to collectively appear as a decorative object. For example, the embodiment illustrated in FIG. 12 is formed to appear as a house. The decorative object may include, but is not limited to, variations representing animals, such as dogs and cats, candles, plants, a barber pole, and toy figurines, just to name a few. As one with skill in the art will appreciate, the primary compartment **100**, the secondary compartment **200**, and the  
20 cover **300** may be virtually any shape and profile, therefore the assortment of potential decorative objects and sizes are virtually endless.

Now, with the apparatus **50** described in detail, the method for its use will be addressed. As all adults know, build-up **BU** of minerals and other impurities occurs in a toilet bowl **TB** at

the interface between the liquid **W** and the toilet bowl **TB**. This build-up **BU** is often difficult to remove in part due to the fact that most cleaning fluids are quickly diluted in the liquid **W** that remains in the toilet bowl **TB** during cleaning. The cleaning brush **B** then merely sloshes around the diluted mixture while attempting to scrape away the build-up **BU**. The cleaning effectiveness is greatly improved by reducing the amount of liquid in the toilet bowl **TB** so that the water level **WL** is significantly below the level of the build-up **BU** ring.

The reduction in the water level **WL** is accomplished through the use of the present invention. Further, one is not required to have any knowledge of plumbing systems to effectively use the present invention. The first step in the process is to remove the cover **300** from the primary compartment **100** and remove the brush **B**. Next, the goal is to fill the primary compartment **100** with water to a desired level, indicated by the plurality of indicia **190** marked in the interior surface **150**. The plurality of indicia **190** may consist of a number of lines indicating the level to which the primary compartment **100** must be filled to work effectively with differing toilets. For instance, one of the plurality of indicia **190** lines may represent the level that is effective for the newer low-consumption 1.6 gallon per flush toilet, whereas another may represent the level that is effective for older toilets that consume in excess of 2 gallons per flush. The aforementioned indicia allow a user, after a brief trial and error experimentation, to know and to reproduce the optimal amount of water needed for operation in his or her own fixtures. The primary compartment **100** may be filled either by utilizing a shower or bathtub faucet, or by using the secondary compartment **200** to fill the primary compartment **100**. The secondary compartment **200** is primarily used in half-bath bathrooms only having a lavatory faucet as a source of water. In such a situation the secondary compartment **200** is repeatedly filled with water from the lavatory faucet that is then transferred to the primary compartment

**100.** The new and novel design of the present apparatus **50** makes it equally effective, and convenient, for half-bathrooms and full bathrooms.

Once the primary compartment **100** is filled to the desired level, the user holds the primary compartment **100** by the gripping device **180** over the toilet bowl **TB** and begins rapidly  
5 pouring the contents into the toilet bowl **TB**, as shown in FIG. 6. The toilet bowl **TB** and trap **TR** temporarily rise above their normal water level **WL** and the siphonic cycle begins. A majority of the water in the toilet bowl **TB** is sucked through the trap **TR**. The siphonic cycle ends when the water drains sufficiently for air to break the siphon in the trap **TR**. As one with skill in the art can appreciate, when using this method no additional water enters the toilet bowl from the toilet  
10 tank, as would be the case in a normal flush cycle. Therefore, the new water level **WL** in the toilet bowl **TB** is significantly below the level of the build-up **BU**, as seen in FIG. 7, thereby permitting easy cleaning of the toilet bowl **TB**. When cleaning is complete, a simple flush of the tank mechanism will evacuate the cleaning materials and bowl contents, and restore the water level to the normal predetermined level.

15 The material and construction of the components of the apparatus **50** is selected to be an impact resistant and durable material that resists abrasion wear and that can withstand exposure to deleterious fluids and substances, such as, without limitation, biological, and commercial cleaning fluids and substances. Some such exemplary substances and fluids include high temperature water, cleaning and disinfecting fluids, biological fluids, bacteria, and fungi, to  
20 name a few. The apparatus **50** may further include an antimicrobial agent, which may form a surface coating on at least the primary compartment interior surface **150** and the secondary compartment interior surface **250**, to reduce, or eliminate, the build-up of undesirable elements in the apparatus **50**.

Numerous alterations, modifications, and variations of the preferred embodiments disclosed herein will be apparent to those skilled in the art and they are all anticipated and contemplated to be within the spirit and scope of the instant invention. For example, although specific embodiments have been described in detail, those with skill in the art will understand  
5 that the preceding embodiments and variations can be modified to incorporate various types of substitute and or additional or alternative materials, relative arrangement of elements, and dimensional configurations. Accordingly, even though only few variations of the present invention are described herein, it is to be understood that the practice of such additional modifications and variations and the equivalents thereof, are within the spirit and scope of the  
10 invention as defined in the following claims. The corresponding structures, materials, acts, and equivalents of all means or step plus function elements in the claims below are intended to include any structure, material, or acts for performing the functions in combination with other claimed elements as specifically claimed.